NMC-WOLLARD Model 60 Tow Tractor

3,000 to 6,000 lbs. drawbar pull Economical baggage tractor




- DBP from 3,000 to 6,000 lbs. (1,360 to 2,721 kg)
- Maximum load capacity: 60,000 lbs. (27,216 kg)
- Rugged. Front bumper is massive 1" (2.5 cm) thick steel plate.
- Has rugged drive axle and frame.
- Easy to maintain.




- Automatic transmission
- Power-assisted 4-wheel brakes
- Power steering
- Front & rear spring suspension
- Heavy-duty 3/4" precision aligned 1-piece frame

NMC-WOLLARD Model 60 Tow Tractor

Specifications based on standard drive train and are subject to change without notice. Photos and illustrations may show optional equipment.





Capacities & Weights

Model No.	6003	6004	6005	6006	Model No.	6003	6004	6005	6006
Drawbar pull in lbs: Drawbar pull in kg:	3,000 1,360	,	- /	-)	Gross wt. in lbs: Gross wt. in kg:	,	5,600 2,540	- ,	,

Dimensions & Data

Length	102" (259 cm)		
Width	55" (140 cm)		
Height w/o cab	61.5" (156 cm)		
Height w/ cab	85.5" (217 cm)		
Turn Radius	135" (343 cm)		
Ground Clearance, less axles8" (20 cm)			
Speed, F12-2	20 mph* (19-32 km/h)		
R	.5-7 mph (8-11 km/h)		
*Consult factory for speeds			

Power

Power options include: Gas LPG CNG Diesel

Consult factory for details

Transmission: Automatic with separate transmission fluid cooler Options: consult factory

Cooling System: Full Size. Engine radiator insulated from vibration.

Drive Axle: double reduction type with drop box spur gear set.

Steering Axle: Heavy-duty tubular with inclined king pins and caster for tracking and turning. Hydrostatic power steering.

Suspension: Drive axle and steer axle: Semi-elliptical leaf spring

Brakes: Power assisted 4-wheel vented disc brakes with dual master cylinder Drum brakes with dual tires.

Tires:	Front:	Radial ST175/80R13
	Rear:	8.75 X 16.5
	Dual Drive:	LT215/85R16

Electrical: 12 V, neg. ground 66+ amp alternator

Instrumentation Gauges include: voltmeter, coolant temperature, engine oil pressure, fuel level, transmission oil temperature, engine hour meter.

Frame: Heavy Duty 3/4" precision aligned 1-piece structure

Fuel Capacity: 20.7 gal.; 78.3 liters.

Standard Equipment:

Automatic transmission Gauges: full instrumentation Lights: 2 head, tail and stop Paint: white or safety yellow Power-assisted 4-wheel brakes Power steering Front & rear spring suspension Seat belts

Optional Equipment:

Back-up alarm Cab assembly — all weather Dual wheels Econocab Heater/defroster LP fuel Mirror kit Overhead guard Passenger seat Rotating beacon, amber Safety shutdown Turn signals Spark arresting muffler

Note: Special drive trains and other options available upon request.

GVW may vary ± 5% DBP measured @ 12" (30.5 cm)

NMC-WOLLARD

 2021 Truax Blvd, Eau Claire, WI 54703

 Phone:
 800-656-6867

 Phone:
 715-835-3151

 Fax:
 715-835-6625

 Email:
 info@nmc-wollard.com

 Website:
 www.nmc-wollard.com

9/12

Dealer/Distributor