

Classic

Model HTA (3,000 lb to 6,000 lb Drawbar pull)



Standard Features

- F-N-R shifter
- Keyless anti-restart ignition switch
- Two Headlights
- Combination Tail/Stop Lights & Back-up Light
- Volt Meter
- Water Temperature Gauge
- Engine Oil Pressure Gauge
- Engine Hour Meter Gauge
- Fuel Level Gauge
- Standard driver and passenger seat

Specifications subject to improvement and/or change without notice

Specifications for Model: Classic (3k-6k) Towing

Drawbar Pull Available

<u>Model</u>	<u>DBP</u>	<u>(+/-)GVW</u>	<u>(+/-) Towed Wt</u>
HTA30.....	3,000 lbs4,000 lbs 30,000 lbs
HTA40	4,000 lbs5,250 lbs 40,000 lbs
HTA50	5,000 lbs6,500 lbs 50,000 lbs
HTA60	6,000 lbs7,200 lbs 60,000 lbs

Towed weight on a dry surface up to a 3% grade

Dimensions

Length	112" (2845 mm)
Width.....	55.5" (1410 mm)
Height.....	63" (1600 mm)
Height w/cab.....	84" (2134 mm)
Wheel Base.....	70" (1778 mm)
Ground Clearance.....	6" (152 mm)

Available Diesel Engines

Equipped with Gauge & Sender system

- *Cummins*
- *Perkins*
- *Deutz*

Available Gasoline (3k – 5k only)

- *GM*

Drive Axle

- Heavy duty Harlan—10,000 lb Load Capacity

Steer Axle

- Heavy duty Harlan with 1 1/8" King Pin

Suspension

- Leaf Springs on front and rear axles

Brakes

Service:

- Dual Split System
- Hydraulic/Hydraulic
- Dual rear disc w/optional front disc brakes
- Other brake options available upon request

Parking:

- Mechanical Drum (lever activated)

Towing Coupler

- E-Hitch – 1" Pin
- Other couplers available on request

Transmission

- Ford C-6 Automatic
- 3-speeds forward, 1 reverse

Electrical

- 12 V, Negative ground

Cooling System

- Liquid cooled 8.5 quart capacity radiator with integral transmission cooler
- Oil cooled radiator with the Deutz engine

Steering System:

- Hydraulic Steering (Saginaw power assisted)

Turning Radius

- 135" (3429mm)

Tires

- Front: 6.50 x 10
- Rear: LT215/80R x16