

Streamline Cargomaster

**Model HTLP (8,000 lb Drawbar pull)
(35.59 kN)**



Shown with options

Standard Features

- F-N-R shifter
- Keyless anti-restart ignition switch
- Two Headlights (recessed)
- Modular lighting includes: Tail/Stop Lights, Backup Light & Turn Signals
- Volt Meter
- Water Temperature Gauge
- Engine Oil Pressure Gauge
- Engine Hour Meter Gauge
- Fuel Level Gauge
- Standard driver and passenger seat
- Driver Hitch Release

27 Stanley Road * Kansas City, Kansas 66115 * USA

913-342-5650 * 800-255-4262 * Fax 913-321-5802

sales@harlan-corp.com

www.harlan-corp.com

Specifications For Model: STREAMLINE 8,000 lb (35 kN)DBP

MODEL	HTLP8o
DBP	8000 lbs (35.59 kN)
Approx. GVW	10000 lbs (4536 kg)
Towed weight +/-	80000 lbs (36290 kg)

Dimensions

Length	117" (2972 mm)
Width	67" (1702 mm)
Height	61" (1549 mm)
Height with cab	81" (2070 mm)
Wheel Base	70" (1778 mm)
Ground Clearance	6" (152 mm)
Turning Radius	120" (3048 mm)

Chassis

Drive Axle	Heavy-duty Harlan – 8200lb (3719 kg) load capacity
Steer Axle	Heavy-duty Harlan with 1 1/8" king pin
Suspension	Shocks and Leaf Springs on front and rear axles
Towing Coupler	Three-tier hitch Front and Rear with 1 3/4" pin
Tires	Front: 6.50 x 10 Dual Rear: LT215/85R x 16

Engine Options

Manufacturer - Diesel	Perkins, Cummins
Manufacturer - Gasoline	Ford 300 – remanufactured to new (restrictions apply)

Travel/Performance

Transmission	C-6 Automatic – 3 speeds forward 1 reverse (remanufactured by a certified re-builder)
Electrical	12 V Negative Ground
Cooling System	Liquid cooled dual cross-flow radiator with trans-cooler
Steering System	Power assist
Service Brakes	Dual Split System, Hydraulic/Hydraulic, dual rear disc and single front disc brakes
Park Brake	Mechanical Drum – lever activated